

Dimension Table

Unit:mm

Designated Size	Nominal Diameter A (B)	Inside Diameter ϕd	Outside Diameter ϕD	Rib Position		Center Diameter ϕC	bolt Hole $n-\phi h$	e	Torque Standards for Tightening N·m
				ϕD_1	ϕD_2				
□	15 (1/2)	20	93	28	42	70	4- $\phi 15$	2.0	15
□	20 (3/4)	25	98	33	47	75	4- $\phi 15$	2.0	30
□	25 (1)	30	123	38	53	90	4- $\phi 19$	3.0	30
□	30 (1.1/4)	38	133	48	63	100	4- $\phi 19$	3.0	30
□	40 (1.1/2)	46	138	54	69	105	4- $\phi 19$	4.0	30
□	50 (2)	58	153	68	83	120	4- $\phi 19$	4.0	30
□	65 (2.1/2)	73	173	86	101	140	4- $\phi 19$	4.0	45
□	80 (3)	84	183	98	113	150	8- $\phi 19$	4.0	45
□	100 (4)	106	208	120	138	175	8- $\phi 19$	4.0	45
□	125 (5)	131	248	145	168	210	8- $\phi 23$	5.0	55
□	150 (6)	155	278	170	196	240	8- $\phi 23$	5.0	55
□	200 (8)	204	328	218	248	290	12- $\phi 23$	5.0	55
□	250 (10)	254	398	270	306	355	12- $\phi 25$	5.0	65
□	300 (12)	304	443	324	356	400	16- $\phi 25$	5.0	65